



SEI GRAFFITI REMOVER SYS GR-SYS

Product Description:

GR-SYS utilizes the SEI Migratory Technology™ that penetrates and chemically fractures the molecular bonds in paints, lacquers, enamels and stains. The GR-SYS active ingredient migrates and penetrates paints, coatings or unwanted marks and creates molecular space between the vandalism and the substrate, making the removal easy from any surface that has been protected with the SEI Graffiti Proofer®, SEI Graffiti Proofer & Curing Agent and the SEI Graffiti Proofer Anti-Stick. GR-SYS has no chemical, physical, mechanical or aesthetic effects on any of the SEI Graffiti Proofers. The stripping time varies from thirty seconds to four minutes, depending on the type of graffiti and number of coatings to be removed.

GR-SYS is a solvent based cleaner that is VOC exempt in regulated consumer products and is not hazardous. This product has been evaluated and it meets the low vapor pressure (LVP) exemption set by the California Air Resources Board for volatile organic compounds in consumer products.

GR-SYS was formulated as a semi-viscous product for applications on vertical and horizontal surfaces or on those of complex geometry. GR-SYS is a multi-purpose formulation and is effective on different types of paints, coatings, lacquers, enamels, waxes and stains but has no effect on the SEI Graffiti Proofers. GR-SYS will remove a wide variety of paints, graffiti and vandalism on a wide variety of unprotected surfaces as well.

Chief Advantages:

- Low odor.
- VOC, AQMD, and CARB compliant.

Packaging:

12oz., 24oz. Aerosol
5-gal, 55-gal
Custom packaging available

Method of Application:

GR-SYS should be applied in full strength. Sufficient time (between thirty seconds and two minutes) should be allowed for the product to migrate and penetrate the graffiti. After sufficient time has past simply wash the GR-SYS and the graffiti away using a water flushing, rag or brush.

DISCLAIMER:

The information provided is to be used as a guide and users should perform their own tests to ensure performance in their application. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. All statements, technical information and recommendations contained herein are based on tests SEI Chemical believes to be reliable, but the accuracy or completeness thereof is not guaranteed. SEI Chemical warrants SEI products will be free from defects when shipped to customer. SEI Chemical's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify SEI Chemical of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer. SEI Chemical shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of SEI Chemical. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose in no case shall SEI Chemical be liable for incidental or consequential damages. Limited warranty, for industrial use only. Keep out of reach of children. Keep containers tightly closed, not for internal consumption, consult material. Consult Material Safety Data Sheet for more information.